

Europäisches Patentamt European Patent Office Office européen des brevets



(11) EP 0 745 329 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication: 04.12.1996 Bulletin 1996/49

- (51) Int Cl.6: A23F 5/24
- (21) Application number: 96201486.6
- (22) Date of filing: 29.05.1996
- (84) Designated Contracting States: BE DE DK ES FR GB GR IT NL
- (30) Priority: 29.05.1995 NL 1000450
- (71) Applicant: Sara Lee/DE N.V. 3532 AA Utrecht (NL)
- (72) Inventors:
 - Kaper, Louris
 3772 ZC Barneveld (NL)

- Peters, Antonius Johannes Maria 5321 RR Hedel (NL)
- (74) Representative: Smulders, Theodorus A.H.J., Ir. et al

Vereenigde Octrooibureaux Nieuwe Parklaan 97 2587 BN 's-Gravenhage (NL)

- (54) Carbonated coffee beverage
- (57) The invention relates to a carbonated coffee beverage which has been packaged under pressure in a pressure-resistant closed container, which beverage

is based on coffee extract, the coffee beverage having been packaged in the closed container in the presence of $\rm CO_2$ and nitrogen, which beverage preferably contains sugar and/or sweetener.

30

Description

The invention relates to a carbonated beverage which has been packaged under pressure in a pressure-resistant closed container.

1

Carbonated soft drinks packaged under pressure in cans are produced and sold on a large scale. The greater part of this market consists of lemonades, such as coke, soft drinks with a fruit flavour and the like. There is also a clear interest in cooled tea, optionally slightly carbonated and/or provided with a supplementary fruit flavour and/or sweetened.

It is also known to package coffee in cans, for consumption, for instance as ice coffee. In practice, this ice coffee is optionally sweetened and is optionally slightly carbonated. The presence of carbon dioxide in the coffee is primarily intended to provide the prickly effect which carbon dioxide is known to have. It also provides a layer of foam on the coffee after it has been poured out. The structure of this layer of foam is comparable to the structure of the foam on espresso coffee.

It is also known to package non-foaming beverages, such as tea, coffee, and fruit juice in cans in the presence of nitrogen gas and carbon dioxide gas. This combination of gases is intended to provide a thin metal package with sufficient internal pressure, so that the package has sufficient strength.

The above application involves non-carbonated (non-fizzy; non-sparkling) beverages, which means that the carbon dioxide content of the liquid is not greater than 0.15% by weight.

The object of the invention is to provide an improved type of packaged coffee drink (coffee extract), which improvement relates especially to the taste, and to a lesser extent to the foaming.

Surprisingly, it has been found that the quality and especially the taste of the carbonated coffee beverage which has been packaged under pressure in a pressure-resistant container, which beverage is based on coffee extract, with the coffee beverage having been packaged in the closed container, can be improved by the presence of nitrogen in the package.

Accordingly, the invention relates to a carbonated coffee beverage which has been packaged under pressure in a pressure-resistant closed container, which beverage is based on coffee extract, the coffee beverage having been packaged in the closed container in the presence of CO₂ and nitrogen.

The improvement of the taste is particularly surprising, since it was not known that the presence of nitrogen, known to be a highly inert gas, might have any influence on the taste. It has been found that the taste of the coffee becomes creamier and less sharp, while this taste at the same time becomes richer in character.

According to the invention, the beverage consists of coffee extract (coffee), optionally supplemented with conventional additions, such as sugar, sweeteners, nutrient acid and the like. It is also possible to add supple-

mentary flavour components to the beverage, such as cinnamon, cocoa, rum flavour, fruit flavours and the like.

The coffee extracts to be used can have been obtained in a known manner by extraction of roasted coffee, and supplemented with water to the desired strength. If desired, one can also start from a wholly or partly decaffeinated coffee, or from a blend of decaffeinated and non-decaffeinated coffee.

Optionally, the beverage can also be supplemented with an amount of alcoholic beverage, such as rum, whisky, and the like. It is possible to add milk or milk products to the beverage. If desired, it is also possible to add so-called whiteners, which are not based on milk.

According to a preferred embodiment of the invention, the contents of the container consist substantially of coffee extract, water, CO₂, nitrogen, optionally in combination with aromatic, flavouring and sweetening substances.

The mutual proportions of the various components of the coffee beverage can be chosen fairly broadly, the eventual composition being partly dependent on the desired taste of the coffee drink. The amount of gas in the container (carbon dioxide and nitrogen) is chosen such that the pressure in the package is minimally at the level required for the strength of the package. A conventional pressure at room temperature is between 1.01 and 7.0 bar. In case pasteurization is to take place, the maximum pressure is preferably not higher than 3.0 bar. In this connection, it is noted that in the thin cans currently used, an internal pressure is necessary to impart the desired strength to the cans.

According to the invention, such an amount of nitrogen is added that the pressure at 20° C is 0.2 to 2.0 bar higher than the pressure existing as a result of the addition of CO_2 and which can vary from 0.5 to 5.0 bar.

The invention is specifically directed to foaming or effervescent (fizzy, sparkling) coffee, which means that the content of $\rm CO_2$ dissolved in the liquid is greater than 0.15% by weight, more particularly greater than 0.25% by weight (based on the weight of $\rm CO_2$ with respect to the total weight of the liquid).

In practice, it has been found that it is not easy to determine the proper dosage of nitrogen.

In a number of types of coffee extract, an (unpredictable) excessive foaming can occur. It has been found that a good and predictable foaming behaviour is obtained by adding from 0.5 to 10 ppm foam inhibiting agent, typically based on polysiloxanes, such as dimethyl siloxane.

It has additionally been found that another advantage of the invention resides in the fact that the use of nitrogen in the pressurized package gives an improvement of the structure of the foam layer. The consumer sometimes prefers that with ice coffee, after it has been poured out, a foam layer is present on the coffee. It is true that the presence of carbon dioxide in the package already gives rise to some foaming, but the amount and the structure of the foam are not satisfactory if carbon

5

10

15

35

4

dioxide alone is used. By the co-use of nitrogen, the amount and the nature of the foam have been found to have clearly improved. In this connection, it is noted that it is known that nitrogen can effect an improvement of the foam structure in carbonated beverages.

For the purpose of packaging the beverage in the package, the conventional packaging techniques can be used, provided that it is ensured that the desired amounts of nitrogen gas and carbon dioxide gas are introduced into the package. This is preferably done immediately before the package is closed, prior to pasteurization. The addition can occur in the form of solid carbon dioxide or liquid nitrogen, but it is also possible to introduce the components into the package in gaseous form under pressure. This last can be done in the form of separate gases or by first mixing the gases in the proper amounts and dosing the mixture under pressure.

The invention will now be further explained in and by some examples, which should not be construed as a limitation of the invention.

EXAMPLE 1

A standard aluminium can of a contents of 0.33 1 was filled with an amount of coffee extract of a 50/50 Arabica/robusta blend, and supplemented with water to the desired strength. Also, an amount of sugar has been added to the contents. Prior to pasteurizing at 62°C, so much carbon dioxide and so much nitrogen were dosed to the contents that these gases, upon cooling, respectively provided a partial pressure of 1.75 and 1.25 bar in the can, with a total pressure of 3.0 bar. The content of dissolved carbon dioxide was 0.35% by weight.

Upon cooling of the can with its contents to a temperature of 4-6°C (refrigerator temperature), the contents were poured out in a cup. A fine foam layer on the surface was observed, of a structure comparable to espresso, which foam layer endured for a prolonged period of time, while the taste of the coffee was excellent.

COMPARATIVE EXAMPLE

For comparison, a can with the same components was fabricated, except that the nitrogen had been omitted. Upon cooling to refrigerator temperature, the contents were likewise poured out in a cup. In comparison with the previous test, the taste was clearly poorer, that is, a less rich, sharper taste, which moreover was less creamy. The foam layer was highly irregular and endured only for a short time.

EXAMPLE 2

Example 1 was repeated, but instead of the coffee extract a decaffeinated coffee extract of a comparable blend was used. As sweetener, a conventional synthetic sweetener was used, such as aspartame, cyclamate and/or saccharin.

Thus, a calorie-free decaffeinated coffee beverage was obtained, which, consumed cool, represented an excellent ice coffee, comparable in quality with the coffee of Example 1.

Claims

- A carbonated coffee beverage which has been packaged under pressure in a pressure-resistant closed container, which beverage is based on coffee extract, and wherein the coffee beverage has been packaged in the closed container in the presence of CO₂ and nitrogen.
- A carbonated beverage according to claim 1, which beverage also contains sugar and/or sweetener.
- A carbonated beverage according to claim 1 or 2, wherein the contents of the container consist substantially of coffee extract, water, CO₂, nitrogen, optionally in combination with aromatizing, flavouring and sweetening substances.
- 25 4. A carbonated beverage according to claims 1-3, wherein the amounts of CO₂ and nitrogen are chosen such that the pressure in the container at room temperature is between 1.01 and 7.0 bar.
- 30 5. A carbonated beverage according to claims 1-4, wherein so much nitrogen is present that the pressure at 20°C is 0.2 to 2.0 bar higher than the pressure which exists as a result of the addition of CO₂ and which can vary from 0.5 to 5.0 bar.
 - A carbonated beverage according to claims 1-5, wherein the container has been made of metal.
 - A carbonated beverage according to claims 1-6, wherein also 0.5 to 10 ppm of foam inhibiting agent is present.
 - 8. Use of nitrogen for improving the taste of carbonated coffee beverage packaged under pressure.



Application Number EP 96 20 1486

	DOCUMENTS CONS	IDERED TO BE RELEVAN	T	
Category	Citation of document with of relevant p	indication, where appropriate, assages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
Х	GB-A-2 134 496 (ASA 1984 * page 3, line 10-	AHI BREWERIES) 15 August 19; claims 1-13 *	1-7	A23F5/24
х	WO-A-93 04590 (AME March 1993 * page 8, line 1-14	RICA NATIONAL CAN CO) 18	1-7	
X	AN 92-099624 XP002012641	ns Ltd., London, GB; (DAIWA SEIKAN KK) , 12	1-7	
x	AN 86-019059 XP002012642	ns Ltd., London, GB;	1-7	TECHNICAL FIELDS SEARCHED (Int.Cl.6)
A	GB-A-2 089 191 (TO) June 1982 * claims 1-9 *	O SEIKAN KAISHA) 23	1-7	
4	US-A-5 384 143 (MAS January 1995 * claims 1-4 *	AHIRO KOYAMA) 24	1-7	
A	CH-A-406 811 (AEROT * column 2, line 42	OM AG) 15 August 1966 - line 56; claim *	1	:
A	FR-A-2 572 708 (JUJ	O PAPER CO) 9 May 1986		·
	The present search report has b	een drawn up for all claims]	
Place of search Date of completion of the search		' 	Examiner	
	THE HAGUE	5 September 1996	Des	medt, G
X : part Y : part docu A : tech O : non-	CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category T: theory or principl E: earlier patent do after the filling d: D: document cited if			ished on, or

EPO FORM 1503 03.82 (P04C01)



Application Number EP 96 20 1486

Category	Citation of document with indication of relevant passages		Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)		
\	FR-A-2 414 877 (SOCIĒTĒ NESTLĒ) * page 1, line 7 - line		1,7			
				TECHNICAL FIELDS SEARCHED (Int.CL6)		
	The present search report has been dr	awn up for all claims				
	Place of search	Date of completion of the search	<u> </u>	Examiner		
THE HAGUE		5 September 19	996 De:	Desmedt, G		
X:par Y:par	CATEGORY OF CITED DOCUMENTS ticularly relevant if taken alone ticularly relevant if combined with another tument of the same category	rinciple underlying the invention at document, but published on, or ling date cited in the application itted for other reasons				



Europäisches Patentamt European Patent Office Office européen des brevets



(11) EP 0 745 329 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication: 04.12.1996 Bulletin 1996/49

- (51) Int Cl.6: A23F 5/24
- (21) Application number: 96201486.6
- (22) Date of filing: 29.05.1996
- (84) Designated Contracting States: BE DE DK ES FR GB GR IT NL
- (30) Priority: 29.05.1995 NL 1000450
- (71) Applicant: Sara Lee/DE N.V. 3532 AA Utrecht (NL)
- (72) Inventors:
 - Kaper, Louris
 3772 ZC Barneveld (NL)

- Peters, Antonius Johannes Maria
 5321 RR Hedel (NL)
- (74) Representative:
 Smulders, Theodorus A.H.J., Ir. et al
 Vereenigde Octrooibureaux
 Nieuwe Parklaan 97
 2587 BN 's-Gravenhage (NL)

(54) Carbonated coffee beverage

(57) The invention relates to a carbonated coffee beverage which has been packaged under pressure in a pressure-resistant closed container, which beverage

is based on coffee extract, the coffee beverage having been packaged in the closed container in the presence of CO_2 and nitrogen, which beverage preferably contains sugar and/or sweetener.

Description

The invention relates to a carbonated beverage which has been packaged under pressure in a pressure-resistant closed container.

Carbonated soft drinks packaged under pressure in cans are produced and sold on a large scale. The greater part of this market consists of lemonades, such as coke, soft drinks with a fruit flavour and the like. There is also a clear interest in cooled tea, optionally slightly carbonated and/or provided with a supplementary fruit flavour and/or sweetened.

It is also known to package coffee in cans, for consumption, for instance as ice coffee. In practice, this ice coffee is optionally sweetened and is optionally slightly carbonated. The presence of carbon dioxide in the coffee is primarily intended to provide the prickly effect which carbon dioxide is known to have. It also provides a layer of foam on the coffee after it has been poured out. The structure of this layer of foam is comparable to the structure of the foam on espresso coffee.

It is also known to package non-foaming beverages, such as tea, coffee, and fruit juice in cans in the presence of nitrogen gas and carbon dioxide gas. This combination of gases is intended to provide a thin metal package with sufficient internal pressure, so that the package has sufficient strength.

The above application involves non-carbonated (non-fizzy; non-sparkling) beverages, which means that the carbon dioxide content of the liquid is not greater than 0.15% by weight.

The object of the invention is to provide an improved type of packaged coffee drink (coffee extract), which improvement relates especially to the taste, and to a lesser extent to the foaming.

Surprisingly, it has been found that the quality and especially the taste of the carbonated coffee beverage which has been packaged under pressure in a pressure-resistant container, which beverage is based on coffee extract, with the coffee beverage having been packaged in the closed container, can be improved by the presence of nitrogen in the package.

Accordingly, the invention relates to a carbonated coffee beverage which has been packaged under pressure in a pressure-resistant closed container, which beverage is based on coffee extract, the coffee beverage having been packaged in the closed container in the presence of CO₂ and nitrogen.

The improvement of the taste is particularly surprising, since it was not known that the presence of nitrogen, known to be a highly inert gas, might have any influence on the taste. It has been found that the taste of the coffee becomes creamier and less sharp, while this taste at the same time becomes richer in character.

According to the invention, the beverage consists of coffee extract (coffee), optionally supplemented with conventional additions, such as sugar, sweeteners, nutrient acid and the like. It is also possible to add supple-

mentary flavour components to the beverage, such as cinnamon, cocoa, rum flavour, fruit flavours and the like.

The coffee extracts to be used can have been obtained in a known manner by extraction of roasted coffee, and supplemented with water to the desired strength. If desired, one can also start from a wholly or partly decaffeinated coffee, or from a blend of decaffeinated and non-decaffeinated coffee.

Optionally, the beverage can also be supplemented with an amount of alcoholic beverage, such as rum, whisky, and the like. It is possible to add milk or milk products to the beverage. If desired, it is also possible to add so-called whiteners, which are not based on milk.

According to a preferred embodiment of the invention, the contents of the container consist substantially of coffee extract, water, CO₂, nitrogen, optionally in combination with aromatic, flavouring and sweetening substances.

The mutual proportions of the various components of the coffee beverage can be chosen fairly broadly, the eventual composition being partly dependent on the desired taste of the coffee drink. The amount of gas in the container (carbon dioxide and nitrogen) is chosen such that the pressure in the package is minimally at the level required for the strength of the package. A conventional pressure at room temperature is between 1.01 and 7.0 bar. In case pasteurization is to take place, the maximum pressure is preferably not higher than 3.0 bar. In this connection, it is noted that in the thin cans currently used, an internal pressure is necessary to impart the desired strength to the cans.

According to the invention, such an amount of nitrogen is added that the pressure at 20°C is 0.2 to 2.0 bar higher than the pressure existing as a result of the addition of CO₂ and which can vary from 0.5 to 5.0 bar.

The invention is specifically directed to foaming or effervescent (fizzy, sparkling) coffee, which means that the content of $\rm CO_2$ dissolved in the liquid is greater than 0.15% by weight, more particularly greater than 0.25% by weight (based on the weight of $\rm CO_2$ with respect to the total weight of the liquid).

In practice, it has been found that it is not easy to determine the proper dosage of nitrogen.

In a number of types of coffee extract, an (unpredictable) excessive foaming can occur. It has been found that a good and predictable foaming behaviour is obtained by adding from 0.5 to 10 ppm foam inhibiting agent, typically based on polysiloxanes, such as dimethyl siloxane.

It has additionally been found that another advantage of the invention resides in the fact that the use of nitrogen in the pressurized package gives an improvement of the structure of the foam layer. The consumer sometimes prefers that with ice coffee, after it has been poured out, a foam layer is present on the coffee. It is true that the presence of carbon dioxide in the package already gives rise to some foaming, but the amount and the structure of the foam are not satisfactory if carbon

35

10

dioxide alone is used. By the co-use of nitrogen, the amount and the nature of the foam have been found to have clearly improved. In this connection, it is noted that it is known that nitrogen can effect an improvement of the foam structure in carbonated beverages.

For the purpose of packaging the beverage in the package, the conventional packaging techniques can be used, provided that it is ensured that the desired amounts of nitrogen gas and carbon dioxide gas are introduced into the package. This is preferably done immediately before the package is closed, prior to pasteurization. The addition can occur in the form of solid carbon dioxide or liquid nitrogen, but it is also possible to introduce the components into the package in gaseous form under pressure. This last can be done in the form of separate gases or by first mixing the gases in the proper amounts and dosing the mixture under pressure.

The invention will now be further explained in and by some examples, which should not be construed as a limitation of the invention.

EXAMPLE 1

A standard aluminium can of a contents of 0.33 1 was filled with an amount of coffee extract of a 50/50 Arabica/robusta blend, and supplemented with water to the desired strength. Also, an amount of sugar has been added to the contents. Prior to pasteurizing at 62°C, so much carbon dioxide and so much nitrogen were dosed to the contents that these gases, upon cooling, respectively provided a partial pressure of 1.75 and 1.25 bar in the can, with a total pressure of 3.0 bar. The content of dissolved carbon dioxide was 0.35% by weight.

Upon cooling of the can with its contents to a temperature of 4-6°C (refrigerator temperature), the contents were poured out in a cup. A fine foam layer on the surface was observed, of a structure comparable to espresso, which foam layer endured for a prolonged period of time, while the taste of the coffee was excellent.

COMPARATIVE EXAMPLE

For comparison, a can with the same components was fabricated, except that the nitrogen had been omitted. Upon cooling to refrigerator temperature, the contents were likewise poured out in a cup. In comparison with the previous test, the taste was clearly poorer, that is, a less rich, sharper taste, which moreover was less creamy. The foam layer was highly irregular and endured only for a short time.

EXAMPLE 2

Example 1 was repeated, but instead of the coffee extract a decaffeinated coffee extract of a comparable blend was used. As sweetener, a conventional synthetic sweetener was used, such as aspartame, cyclamate and/or saccharin.

Thus, a calorie-free decaffeinated coffee beverage was obtained, which, consumed cool, represented an excellent ice coffee, comparable in quality with the coffee of Example 1.

Claims

- A carbonated coffee beverage which has been packaged under pressure in a pressure-resistant closed container, which beverage is based on coffee extract, and wherein the coffee beverage has been packaged in the closed container in the presence of CO₂ and nitrogen.
- A carbonated beverage according to claim 1, which beverage also contains sugar and/or sweetener.
- A carbonated beverage according to claim 1 or 2, wherein the contents of the container consist substantially of coffee extract, water, CO₂, nitrogen, optionally in combination with aromatizing, flavouring and sweetening substances.
- 25 4. A carbonated beverage according to claims 1-3, wherein the amounts of CO₂ and nitrogen are chosen such that the pressure in the container at room temperature is between 1.01 and 7.0 bar.
- 5. A carbonated beverage according to claims 1-4, wherein so much nitrogen is present that the pressure at 20°C is 0.2 to 2.0 bar higher than the pressure which exists as a result of the addition of CO₂ and which can vary from 0.5 to 5.0 bar.
 - A carbonated beverage according to claims 1-5, wherein the container has been made of metal.
- A carbonated beverage according to claims 1-6, wherein also 0.5 to 10 ppm of foam inhibiting agent is present.
 - Use of nitrogen for improving the taste of carbonated coffee beverage packaged under pressure.



Application Number EP 96 20 1486

Category	Citation of document w	ith indication, where appropriate, at passages	Relevant to claim	CLASSIFICATION OF TH
X	1707	ASAHI BREWERIES) 15 August 0-19; claims 1-13 *		APPLICATION (Int.Cl.6) A23F5/24
x		MERICA NATIONAL CAN CO) 18	1-7	
	XP002012641	ons Ltd., London, GB; (DAIWA SEIKAN KK) , 12	1-7	
8	(P002012642	ons Ltd., London, GB; (NIPPON NAT SEIKAN) ,	1-7	TECHNICAL FIELDS SEARCHED (Int.Cl.6) A23F
ĮV	B-A-2 089 191 (TO une 1982 claims 1-9 *	YO SEIKAN KAISHA) 23	1-7	
0	S-A-5 384 143 (MAS anuary 1995 claims 1-4 *	SAHIRO KOYAMA) 24	1-7	
CI *	H-A-406 811 (AEROT column 2, line 42	OM AG) 15 August 1966 1 - line 56; çlaim *		
FF	R-A-2 572 708 (JUJ	O PAPER CO) 9 May 1986		•
Th	e present search report has b	een drawn up for all claims		
	ce of search	Date of completion of the search		
TH	E HAGUE	5 September 1996	Desma	edt, G
: particula : particula documen : technolos	GORY OF CITED DOCUMEN rly relevant if taken alone rly relevant if combined with anot to of the same category ical background en disclosure	TS T: theory or principle on E: earlier patent docume	nderlying the invent, but published	ection d on, ar

EPO FORM 1503 03.82 (P04C01)

a solventita alta silvitat. 🖰 🗀 alt



Application Number EP 96 20 1486

Category	Citation of document with indicate of relevant passages		Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)	
A	FR-A-2 414 877 (SOCIÉTI NESTLÉ) * page 1, line 7 - line	DES PRODUITS 1	.,7		
				TECHNICAL FIELDS SEARCHED (Int. Cl.6)	
		,			
The present search report has been drawn					
	THE HAGUE	Date of completion of the search 5 September 1996	Des	medt, G	
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure		T: theory or principle t E: earlier patent docun after the filling date D: document cited in t L: document cited for	T: theory or principle underlying the Invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons d: member of the same patent family, corresponding		

5